

COOEE 2

CORDLESS TABLE LAMP



DESIGNED & ASSEMBLED
IN AUSTRALIA



5 YEARS
WARRANTY



95+ CRI
LED



ALL PARTS
REPLACEABLE



INTERNATIONAL
DELIVERY



Anodised
Silver
Aluminium



Lacquered
Real Brass



Lacquered
Real Copper



Anodised
Sandblasted Bronze
Aluminium



Anodised
Sandblasted Black
Aluminium




Handling Accessory
6 Lamp Carrier
(Optional)

COOEE 2 - Technical Description

The Cooee 2 rechargeable battery table lamp features a slim durable metal body and cylindrical opal diffuser and top plate providing soft ambient side and downlight. The lamp is fitted with a 1W 95+ CRI LED for superior colour rendering. Digital 3 step dimming.

Designer	Peter Ellis, Tammy Chiew
Year of Design	2013
Lamp Type	Sidelight & Downlight
IP Rating	IP52
Dimensions	210mm x 90mm (8¼" x 3½")
Weight	0.32 kg / 0.70 lb
Approvals & Standards	CE, CSA, C-Tick, FCC, RoHS, SASO
EU Energy Regulation	Exempt - LED lamps operate on batteries
Awards	IDA Design Award GOLD Winner 2013



Lamp Control Unit Options

Type	Battery	Cells	Charge Time	Light Source Option	Colour Temperature (Kelvin)	Operating Time (hours)			Brightness (lumens)	CRI*	Bulb Life (Hours)
						High	Med	Low			
UNO	Panasonic Li-ion 3.7V 2900mAh 500+ cycles	1	5.5hrs	1W LED Warm White (Standard)	2600k	13	35	130	68+	95+	50,000+
				1W LED Warm Candle White (Optional)	1800k	13	35	130	58+	93+	50,000+

COLOUR RENDERING INDEX (CRI) The quantitative measure of the ability of a light source to reproduce the colors of various objects faithfully in comparison with an ideal or natural light source. The highest possible CRI is 100.

POWER SOURCE 100 - 240V Switch-Mode Electronic Power Supply
Approved for worldwide usage supplied with appropriate mains electric plug type

Recharging Options



Single Lamp Charger
1 Lamp



Small Recharging Tray
4 Lamps



Large Recharging Tray
12 Lamps



Small Recharging Station
24 Lamps



Medium Recharging Station
36 Lamps



Large Recharging Station
48 Lamps